

Solvent Gloss Backlight Taklite C151SGBT



Product Data

- Product type:** Polyester film for solvent inkjet printing
- Appearance:** Translucent
- Surface finish:** Gloss printable coated front with a repositionable stick fast backing

Physical characteristics:

		Typical Value	Test method
Front Face Thickness μ		151	Electronic micrometer
Total Thickness μ		195	Electronic micrometer
Total Weight (gsm)		260	Internal method
CIE Coordinates	L*	96	DCI Spectraflash (D65 10' UV incl.)
	a*	- 1	
	b*	5	

Compatibility:

'Eco'solvent inks, Roland Soljet, Mutoh Rockhopper II, Seiko ColorPainter etc.
Solvent inks such as for Grenadier, Vutek etc.
Please make your own assessment though, as solvent inks can vary widely. This is more dependent on ink manufacturer and type than it is on printing machine

Applications and characteristics

- § High-impact backlight with optimum depth and brilliance
- § Front print on high-gloss coating with light-diffusing back-coat
- § Print and post: no lamination necessary
- § Weather- and scuff-resistant
- § **Unique suction-cling properties**
- § Repeat stick and peel for glass, metal, enamel and gloss paint.
- § No residue, even after long term sticking.
- § Ideal for repositionable window displays and Light-box signage

CAUTION: Some laminates such as Formica may cause the cling surface to behave like a permanent adhesive after time.
Not recommended for exterior vehicle use.
Customers should make their own assessment regarding suitability.

Recommended conditions for use: 10'C - 30'C, 30% - 70% RH
for storage: 10'C - 30'C, 20% - 50% RH

Material Handling, and Shelf Life: 18 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.