

Design Jet Double Matt Film F075CDD



Product Data

Product type: Colour Inkjet Film

Appearance: Translucent

Surface finish: Matt coating

Physical characteristics:

	Typical Value	Test method
Total Thickness μ	110	Electronic micrometer
Total Weight (gsm)	127	Internal method

Compatibility:

	Large Format/CAD	
	Dye Inks	Pigment Inks
HP	***	***
ENCAD	***	***
EPSON	***	**
CANON	***	***

*** = Excellent ** = Good * = Fair

Applications and characteristics

- A Specially designed double matt polyester film, aimed at the CAD market, incorporating an ink jet surface and a satin/matt drawing surface.
- Excellent high resolution monochrome and colour images are achieved, which dry quickly and are moisture resistant.
- The drawing surface allows modifications to images printed in reverse.

Recommended conditions for use: 10°C - 30°C, 30% - 65% RH

for storage: 10°C - 30°C, 20% - 50% RH

Material Handling, and Shelf Life: 18 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com