

Universal Clear Aqueous Inkjet Film F102CJC.2ES

Product Data



Issue EU 5-08

Product type: Print receptive polyester film - Aqueous Dye / Pigment Inkjet

Appearance: Clear, water white (with edge striping)

Surface finish: Gloss, slightly textured

Physical characteristics:

Property	Typical Value	Unit	Test Method
Total Thickness	120 +/- 5	μ	Electronic micrometer
Weight	155 +/- 5	g/m ²	Internal method
Opacity	< 12	%	TAPPI T519
Tensile Strength	MD 18 TD 20	KgF/mm ²	ASTM D882-83
Elongation at break	MD 180	%	ASTM D882-83

Compatibility:

	Large Format		Desktop
	Dye Inks	Pigment Inks	
HP	***	**	***
EPSON	***	**	***
CANON	***	**	***

*** = Excellent * = Good * = Fair

Applications and characteristics

Large Format

§ Edge striped for HP

Small Format

§ Always select the highest quality photo glossy paper/film setting available
(Do not use transparency settings)

Recommended conditions for use: 10°C - 30°C, 30% - 65% RH

for storage: 10°C - 30°C, 20% - 50% RH

Shelf Life: 12 Months (under recommended storage conditions).
Store product in original packaging, when not in use.

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2008

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com