

Gloss White Laser Film F106HGD



Product Data

Product type: Stabilised Polyester Laser Film

Appearance: White

Surface finish: Gloss coating both sides

Physical characteristics:

		Typical Value	Test method
Total Thickness μ		106	Electronic micrometer
Total Weight (gsm)		145	Internal method
CIE Coordinates	L*	98	DCI Spectraflash (D65 10° UV incl.)
	a*	2	
	b*	-8	

Compatibility:

Most mono and colour laser printers and copiers.

When printing Polyesters by laser or copier methods the thick paper or film settings and feed trays should be used where available. If print is attempted using normal 80gsm copier paper settings (particularly on high speed machines i.e. greater than 10ppm) it is likely that the material may jam as it is feeding too fast for its material type and the toner may not fuse correctly. Refer to the printer manual for settings for film products.

Applications and characteristics

- § Has a high gloss surface giving a strong vibrant image and can be printed on both sides where equipment allows.
- § Waterproof, greaseproof, wipeable and punchable.
- § Ideal for presentations, covers, and photo images.

Recommended conditions for use: 10°C - 30°C, 50% - 70% RH
for storage: 10°C - 30°C, 20% - 50% RH

Material Handling, and Shelf Life: 24 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com