

# Ultra Backlight Display Film F125CUB



## Product Data

**Product type:** Colour inkjet film

**Appearance:** Translucent

**Surface finish:** Matt coating

## Physical characteristics:

	Typical Value	Test method
<b>Total Thickness <math>\mu</math></b>	175	Electronic micrometer
<b>Total Weight (gsm)</b>	202	Internal method
<b>Opacity</b>	60%	Internal method

## Compatibility:

	Large Format	
	Dye Inks	Pigment Inks
<b>HP</b>	***	***
<b>ENCAD</b>	***	***
<b>EPSON</b>	***	***
<b>CANON</b>	***	***

\*\*\* = Excellent \*\* = Good \* = Fair

Printed images have high water resistance which is optimised with OEM pigment based inks.

**Available in widths up to: 1524mm (60 inches)**

## Applications and characteristics

- Front print and mount for stunning backlit displays.
- Special diffusion filter built into matt inkjet coating hides light elements.

**Recommended conditions for use:** 10°C - 30°C, 30% - 70% RH

**for storage:** 10°C - 30°C, 20% - 50% RH

**Material Handling, and Shelf Life:** 18 Months

**NOTICE** The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitizers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: [kc@sensitisers.com](mailto:kc@sensitisers.com)