

# Hydroprint Transwhite F130HMD



## Product Data

**Product type:** Toner optimised print receptive polyester film

**Appearance:** White

**Surface finish:** Matt antistatic coating both sides

## Physical characteristics:

	Typical Value	Test method
<b>Total Thickness <math>\mu</math></b>	130	Electronic micrometer
<b>Total Weight (gsm)</b>	168	Internal method

## Compatibility:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour, including, for example, HP Laserjet 4xxx and OKI 93xx.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material, which is beyond the rated capabilities of some devices.

## Applications and characteristics

- Matt white film ideal for print-on-demand
- Full colour printable, more suited to simplex POS & signage
- Waterproof, greaseproof, wipeable and punchable
- No lamination necessary
- Best value polyester

**Recommended conditions for use:** 10°C - 30°C, 50% - 70% RH

**for storage:** 10°C - 20°C, 20% - 50% RH

**Material Handling, and Shelf Life:** 24Months

**NOTICE** The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: [kc@sensitisers.com](mailto:kc@sensitisers.com)