

Hydroprint Matt Green Film F130HPG



Product Data

Product type: Toner optimised print receptive polyester film

Appearance: Pastel Green

Surface finish: Matt coating both sides

Physical characteristics:

	Typical Value	Test method
Total Thickness μ	130	Electronic micrometer
Total Weight (gsm)	172	Internal method
Opacity	c. 92%	

Compatibility:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour (although particularly suited to mono), including, for example, HP Laserjet 4xxx, OKI 93xx and Xerox iGen3. On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material, which is beyond the rated capabilities of some devices.

Applications and characteristics

- § It has a smooth matt surface giving a strong dense image with excellent print adhesion and can be printed on both sides where equipment allows.
- § It is waterproof, greaseproof, wipe-able and punch-able.
- § Ideal for tags and labels.
- § Suitable for presentations and signs - no protection necessary!
- § It can also be used to create instruction manuals or documents for use in harsh environments, and replace the need for paper to be printed and then encapsulated.

Recommended conditions for use: 10°C - 30°C, 50% - 70% RH

for storage: 10°C - 20°C, 20% - 50% RH

Material Handling, and Shelf Life: 24 Months

When Stored under recommended storage conditions

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.