

# Hydrosol Matt White Film F155SMW



## Product Data

**Product type:** Polyester film for solvent inkjet printing  
**Appearance:** White  
**Surface finish:** Matt printable coating one side, antistatic reverse

## Physical characteristics:

		Typical Value	Test method
Total Thickness $\mu$		155	Electronic micrometer
Total Weight (gsm)		205	Internal method
Opacity		99.2%	
CIE Coordinates	L*	98	DCI Spectraflash ( D65 10° UV incl.)
	a*	3	
	b*	- 12	

## Compatibility:

'Eco'solvent inks, Roland Soljet, Mutoh Rockhopper II, Seiko ColorPainter etc.

Solvent inks such as for Grenadier, Vutek etc.

Please make your own assessment though, as solvent inks can vary widely. This is more dependent on ink manufacturer and type than it is on printing machine

## Applications and characteristics

- Stable, durable, no-curl banner material
- Anti-reflective matt surface for optimum ink adhesion, scratch- and waterresistance
- Bright white front for optimum contrast, antistatic backing
- Print-to-Go. No lamination necessary, even for outdoor scrollers, if allowed to harden and not attacked
- Highly suitable for scrolling banners and instant roll-up graphics

**Recommended conditions for use:** 10°C - 30°C, 30% - 70% RH

**for storage:** 10°C - 30°C, 20% - 50% RH

**Material Handling, and Shelf Life:** 18 Months

**NOTICE** The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: [kc@sensitisers.com](mailto:kc@sensitisers.com)