

# Hydroprint Gloss Clear Film 182HGC

Provisional Product Data



Issue 7-07

**Product type:** Toner optimised Print receptive polyester film

**Appearance:** Clear film

**Surface finish:** Finely textured, both sides

## Physical characteristics:

	Typical Value	Test method
<b>Total Thickness <math>\mu</math></b>	182	Electronic micrometer
<b>Total Weight (gsm)</b>	248	Internal method
<b>Light Transmission %</b>	88 - 93	DCI Spectrophotometer SF600. Trans 10° observer Measuring 400nm-700nm

## Compatibility:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour, including, for example, HP Laserjet 4xxx, OKI 93xx, and Xerox Nuvera. On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material, which is beyond the rated capabilities of some devices.

## Applications and characteristics:

- § It has a finely textured surface giving a strong dense image with excellent print adhesion and can be printed on both sides where equipment allows.
- § It is waterproof, wipe-able and punch-able.
- § Ideal as a clear transparency film for overhead presentations and creative overlays.
- § High image density ensures excellent projection performance.

**Recommended conditions for use:** 10°C - 30°C, 50% - 70% RH

**for storage:** 10°C - 20°C, 20% - 50% RH

**Material Handling, and Shelf Life:** 24 Months

**NOTICE** The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitizers Group 2007

Kerney Coatings Limited : 44(0)1226 272147 e-mail: ke@sensitizers.com