

# Hydroprint Double Sided Gloss/Matt White F188HGM



## Product Data

**Product type:** Toner optimised print receptive Polyester film  
**Appearance:** White  
**Surface finish:** Gloss one side, Matt the other - Print both sides

## Physical characteristics:

		Typical Value		Test method
Total Thickness $\mu$		183		Electronic micrometer
Total Weight (gsm)		256		Internal method
Gloss		87		Internal method
		<b>G</b>	<b>M</b>	
CIE Coordinates	L*	98	97	DCI Spectraflash ( D65 10° UV incl.)
	a*	1.8	0.8	
	b*	- 7	- 4	

## Compatibility:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour, including, for example, HP Laserjet 4xxx and OKI 93xx.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material, which is beyond the rated capabilities of some devices.

## Applications and characteristics

- It has a smooth matt surface and a gloss surface giving a strong dense image with excellent print adhesion and can be printed on both sides where equipment allows.
- It is waterproof, greaseproof, wipe-able and punch-able.
- Ideal for presentations and signs - no protection necessary!
- It can also be used to create instruction manuals or documents for use in harsh environments, and
- replace the need for paper to be printed and then encapsulated.

**Recommended conditions for use:** 10°C - 30°C, 30% - 70% RH  
**for storage:** 10°C - 30°C, 20% - 50% RH

**Material Handling, and Shelf Life:** 18 Months

**NOTICE** The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.