

Hydroprint Heavy Frost F195HHF



Product Data

Product type: Toner optimised print receptive polyester film

Appearance: Translucent

Surface finish: Matt coating both sides

Physical characteristics:

	Typical Value	Test method
Total Thickness μ	195	Electronic micrometer
Total Weight (gsm)	262	Internal method
Opacity	c. 70%	Internal method

Compatibility:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both colour and mono.

On such machines the users must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Please see above for the thickness in microns and the weight in grams per square metre. Most printers have weight ranges to choose from in driver settings.

Applications and characteristics

- § It has a smooth matt surface giving a strong dense image with excellent print adhesion and can be printed on both sides where equipment allows.
- § It is waterproof, greaseproof, wipe-able and punch-able.
- § No protection necessary!
- § Primarily for backlight applications such as vending machines and menu boards.
- § Also aesthetic presentations such as wine list / menu inserts.

Recommended conditions for use: 10°C - 30°C, 50% - 70% RH
for storage: 10°C - 20°C, 20% - 50% RH

Material Handling, and Shelf Life: 24 Months
When Stored under recommended storage conditions

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.