

Hydroprint Heavy Frost Film F195HHF

F195HHF is a 195µ 2-side aqueous diffuse coated polyester film, optimised for dry toner print applications.

Physical characteristics

Property	Typical Value	Unit	Test Method
Total Thickness	195 +/- 5	µ	Electronic micrometer
Weight	262 +/- 6	g/m ²	Internal method
Opacity	64 +/- 2	%	TAPPI T519
Gloss 60	<4	%	BYK Gardner
Shrinkage	MD <1.3 TD <0.4	%	5 minutes @ 150 C (297mm length)
Tensile Strength	MD 14 TD 15	KgF/mm ²	ASTM D882-83
Elongation at break	MD 115 TD 90	%	ASTM D882-83
Melting Point	250	C	ASTM E794-85

Compatibility:

Suitable for most dry toner (laser/LED) & thermal transfer print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Applications and characteristics:

It has a smooth matt diffused surface giving a strong backlit image with excellent print adhesion and can be printed on both sides where equipment allows.

- Water resistant, wipe-able and punch-able.
- Ideal for presentations and Backlit signs - no protection necessary!
- Also highly suitable for applications, such as, Frosted Binder Covers and Menu or Wine List inserts.

Recommended conditions for use: 10°C - 30°C, 40% - 55% RH
for storage: 10°C - 20°C, 20% - 55% RH

Please return unused product to its original packaging

Shelf Life:

24 months after delivery (under recommended storage conditions)

Rev: EU 11/07

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2011