

Graphic Matt Lightblock Film F209CLPL

Product Data



Issue EU 06-11

Product type: Colour inkjet film

Appearance: White

Surface finish: Matt

Physical characteristics:

Property	Typical Value	Unit	Test Method
Total Thickness	212 +/- 5	μ	Electronic micrometer
Weight	251 +/- 5	g/m ²	Internal method
Gloss 60°	2 +/- 1	%	BYK Gardner
CIE Whiteness Index	>80	CIE WI	ISO 11475 UV inc
Opacity	> 99	%	TAPPI T519
Tensile Strength	MD 3500 TD 3000	psi	ASTM D638

Compatibility:

	Large Format
HP	***
EPSON	***

*** = Excellent * *= Good *=Fair

Applications and characteristics

- BOPP film base, with excellent light blocking properties.
- Fast drying images that are smudge resistant.
- Suitable for pigment inks, using **less than 250%** saturation.
- Ideal for roll-up displays and applications requiring light blocking performance.

Recommended conditions for use: 10°C - 30°C, 30% - 65% RH
for storage: 10°C - 30°C, 20% - 50% RH

Please return product to its original packaging when not in use

Shelf Life: 18 Months (under recommended storage conditions)

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2011

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com