

Hydroprint Matt White Film Non Marking F270HWNM



Product Data

Product type: UVC inkjet and silkscreen polyester film

Appearance: White

Surface finish: Matt printable surface both sides

Physical characteristics:

		Typical Value	Test method
Total Thickness μ		270	Electronic micrometer
Total Weight (gsm)		368	Internal method
CIE Coordinates	L*	99	DCI Spectraflash (D65 10° UV incl.)
	a*	4	
	b*	- 13	

Compatibility:

Suitable for UVC inkjet printers and silkscreen printing equipment.

Kernow Hydroprint films deliver all the dimensional stability and colour advantages of polyester being tearproof, waterproof and having the added benefit of surface coatings that improve ink adhesion, a real challenge with UVC inkjet printers.

Especially to be recommended where the product will be repeatedly handled and rolled. In addition, anti-static additives improve runnability for automatic machines.

Applications and characteristics

- § It has a smooth matt surface giving a strong dense image with **enhanced print adhesion** and can be printed on both sides where equipment allows.
- § It is waterproof, greaseproof, wipe-able and punch-able.
- § Ideal for presentations and roll-up banners - no protection necessary!
- § Non Marking properties, especially useful for handling on flat-bed printers
- § Highly anti-static for improved runnability on high speed machines

Recommended conditions for use: 10°C - 30°C, 50% - 70% RH

for storage: 10°C - 20°C, 20% - 50% RH

Material Handling, and Shelf Life: 24 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com