

Hydroprint Matt White Film F270HWT



Product Data

Product type: Toner optimised print receptive polyester film

Appearance: White

Surface finish: Matt coating both sides

Physical characteristics:

		Typical Value	Test method
Total Thickness μ		270	Electronic micrometer
Total Weight (gsm)		368	Internal method
CIE Coordinates	L*	99	DCI Spectraflash (D65 10° UV incl.)
	a*	4	
	b*	- 13	

Compatibility:

Suitable for thermal transfer and dry toner (laser/LED/flash fusion) print processes, both colour and mono, on equipment designed to handle this type of heavyweight film.

On such machines the users must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Please see above for the thickness in microns and the weight in grams per square metre. Most printers have weight ranges to choose from in driver settings

Applications and characteristics:

- It has a smooth matt surface giving a strong dense image with excellent print adhesion and can be printed on both sides where equipment allows.
- It is waterproof, greaseproof, wipe-able and punch-able.
- Ideal for presentations and signs where stiffness is important without lamination.
- It can also be used for a range of applications such as rugged instruction manuals or documents for use in harsh environments.

Recommended conditions for use: 10°C - 30°C, 50% - 70% RH

for storage: 10°C - 20°C, 20% - 50% RH

Material Handling, and Shelf Life: 24 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.