

Instant Drying Photo Gloss Adhesive Paper L280CPDP



Product Data

Product type: Instantly drying self adhesive photo quality ink jet paper

Appearance: White

Surface finish: Gloss coating

Physical characteristics:

		Typical Value	Test method
Total Thickness μ		285	Electronic micrometer
Total Weight (gsm)		245	Internal method
Gloss		60	BYK Gardner 60°
Opacity		>95	DCI Spectraflash (D65 10° UV incl.)
CIE Coordinates	L*	97	DCI Spectraflash (D65 10° UV incl.)
	a*	5	
	b*	- 14	

Compatibility:

	Large Format		Desktop	
	Dye Inks	Pigment Inks	Dye Inks	Pigment Inks
HP	***	X	***	X
EPSON	***	X	***	X
CANON	***	X	***	X
ENCAD	X	X		

*** = Excellent * *= Good *=Fair

Applications and characteristics

- Unique Instant Drying properties.
- Can be mounted to make display panels but images should be left for 24 hrs beforehand.
- Usually prints best in Best-coated paper modes, which also prints twice as fast as most Glossy Paper modes.
- Photo Quality glossy waterfast images immediately (Exception, HP pigment black).
- Pigment inks will image, but some particles may not penetrate, in this case, laminate.

Available in 914mm

Recommended conditions for use: 10°C - 30°C, 30% - 70% RH

for storage: 10°C - 20°C, 20% - 50% RH

Material Handling, and Shelf Life: 18 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com