

# Dark Fabric Inkjet Transfer Paper P141CDT



## Product Data

**Product type:** Colour inkjet transfer paper  
**Appearance:** White – with blue grid backing  
**Surface finish:** Matt Coating

## Physical characteristics:

	Typical Value	Test method
Total Thickness $\mu$	225	Electronic micrometer
Total Weight (gsm)	190	Internal method

## Compatibility:

	Desktop	
	Dye Inks	Pigment Inks
HP	**	**
EPSON	**	**
CANON	***	***

\*\*\* = Excellent \*\* = Good \* = Fair

## Available in A4 and A3 sizes

## Applications and characteristics:

- § Superb coloured images on a white background are ideal for dark T shirts and other 100% cotton fabrics.
- § No special inks are needed but to achieve optimum results please follow the instructions on the following page.
- § Garments are machine washable

**Recommended conditions for use:** 10'C - 30'C, 30% - 70% RH  
**for storage:** 10'C - 25'C, 20% - 50% RH

**Material Handling, and Shelf Life:** 24 Months

**NOTICE** The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: [kc@sensitisers.com](mailto:kc@sensitisers.com)



Issue Date : 17 August 2006

## Dark Fabric Transfer Paper P141CDT

*Produce photo-quality colour transfers with your ink jet printer.*

Print and transfer colour photos and creative designs on t-shirts and other cotton fabrics using your Web-downloaded, scanned, floppy/CD, or digital photo images.

### PRINTING & TRANSFERING using an Iron

#### 1. Printing and Preparing Image.

- The plain white surface is the imaging side of the paper.
- Print the design on the imaging side of the paper with correct orientation (not as a mirror image).
- Printer settings: Select 'normal' or 'plain paper' and 300dpi (HP) or 360dpi (Canon & Epson).
- Single-sheet feeding is recommended.

#### 2. Cut Out Design.

- Do not leave a margin around edge of image.
- Use an image with rounded edges to avoid corner lift-off after washing.

#### 3. Peel Off Grid Backing Paper.

- Remove backing by carefully tearing a corner and peeling away from the face /image

#### 4. Preparing for Transfer.

- Heat iron (without steam) to maximum cotton setting.
- If iron has steam nozzles, use area without nozzles for even heat transfer.
- Fabric should be 100% cotton; iron first if necessary to ensure flatness.
- Let fabric cool before ironing transfer image; lay fabric on hard, smooth surface.
- Place transfer paper with design facing upwards in desired position on fabric.
- Cover image with enclosed tissue paper.

#### 5. Ironing /Transferring Image.

- See table for ironing times; be sure to keep iron constantly moving.
- First apply hot, dry iron at light pressure to fix image in position.
- Then iron at firm pressure in straight, non-stop motion top-to-bottom, or side-to-side.

#### 6. Peel & Wear.

- Allow fabric to cool completely, then smoothly and evenly peel away tissue paper.
- Touch up portions of image by covering with tissue paper again and ironing over area(s).
- Allow fabric to cool completely, then carefully peel away tissue paper.

Ironing Times		
Sheet size	Light iron pressure	Firm iron pressure
1/8 page	30 sec.	
1/4 page	30 sec.	30 sec
1/2 page	1 min	1 min
Full page	1.5 min	1.5 min

### OTHER INFORMATION

- Adult supervision is recommended for children; use in a well-ventilated area.
- Not recommended for HP DeskJet 1200C or 1600C models because they apply heat.
- Before printing final image, produce on economy grade paper to test for layout/design.
- Leave finished item for at least 24 hours before washing. Wash garment prior to wearing first time.
- Fabrics may then be machine washed separately (inside out, with other darks) in cold water.
- Do not tumble-dry or dry-clean.
- Keep product in closed package between uses; store in a cool, dry place.
- After repeated washing, image may begin to diminish; simply re-iron with tissue paper (do not iron directly on image) to bring back to life.

### NOTE

**Special tissue paper is supplied in a ratio of 1 sheet for every 5 sheets of transfer paper**

**NOTICE** The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: [kc@sensitisers.com](mailto:kc@sensitisers.com)