

Instant Drying Photo Glossy Paper P166CPDG



Product Data

Product type: Instantly drying photo quality inkjet paper

Appearance: White

Surface finish: Gloss inkjet coating

Physical characteristics:

		Typical Value	Test method
Total Thickness μ		250	Electronic micrometer
Total Weight (gsm)		166	Internal method
Gloss (60°)		55	BYK Gardner 60°
CIE Coordinates	L*	95	DCI Spectraflash (D65 10° UV incl.)
	a*	- 0.6	
	b*	-18	

Compatibility:

	Desktop	
	Dye Inks	Pigment Inks
HP	***	**
EPSON	***	**
CANON	***	**

*** = Excellent * *= Good *=Fair

Applications and characteristics

- § Unique Instant Drying properties and excellent stiffness for the weight.
- § The high gloss finish is suited to dye based and pigment inks
- § (such as Epson Durabrite and Ultrachrome)
- § Digital photo reproduction and enlargements, presentations, graphic design

Recommended conditions for use: 10°C - 30°C, 30% - 70% RH

for storage: 10°C - 25°C, 20% - 70% RH

Material Handling, and Shelf Life: 24 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2007

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com