

Polymeric PhotoSatin P184CPS



Product Data

Product type: Colour Inkjet Film (polypropylene)
Appearance: Opaque white
Surface finish: Satin inkjet coating with matt anti-slip coating on reverse

Physical characteristics:

	Typical Value	Test method
Total Thickness μ	200	Electronic micrometer
Total Weight (gsm)	185	Internal method
Whiteness	94%	Internal method
Opacity	> 85%	Internal method

Compatibility:

	Large Format	
	Aqueous Dye Inks	Aqueous Pigment Inks
HP	***	**
CANON	***	X
EPSON	***	X
ENCAD	**	X

*HP pigment inks produce slightly less vibrant colours hence the ** rating.*

Available in widths up to: 1524mm (60 inches)

Applications and characteristics

- A low cost alternative to photobase paper also giving savings on ink.
- Saturated vibrant colours achieved with lower ink loadings, allowing faster drying times.
- It is tear resistant and can be grommeted and sewn.
- Excellent for indoor applications.
- Photo reproduction and enlargements.
- Point of Purchase, Signs, Banners and Murals.
- Can also be used for backlit displays.

Recommended conditions for use: 10°C - 30°C, 30% - 60% RH

for storage: 10°C - 25°C, 20% - 60% RH

Material Handling, and Shelf Life: 18 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.