

Gloss White Adhesive Film S051CGWXF



Product Data

Product type: Self Adhesive Colour Inkjet Film

Appearance: White - with film release

Surface finish: Gloss coating

Physical characteristics:

		Typical Value	Test method
Front Face Thickness μ		77	Electronic micrometer
Total Thickness μ		165	Electronic micrometer
Total Weight (gsm)		190	Internal method
Gloss		> 97	Internal method
CIE Coordinates	L*	96	DCI Spectraflash (D65 10° UV incl.)
	a*	1.4	
	b*	- 6.7	

Compatibility:

	Large Format		Desktop
	Dye Inks	Pigment Inks	
HP	***	**	***
ENCAD	***	**	X
EPSON	***	**	***
CANON	***	**	***

*** = Excellent * *= Good *=Fair

Applications and characteristics

- Brilliant quick drying images.
- Standard acrylic adhesive, initially re-positionable, but with increasing strength to stay on permanently except in abrasion and extreme sun.
- Always select the highest quality photo glossy paper/film setting available.
- **Note***- some older HP printers default to pigment black ink for plain black paragraph text, to avoid this problem incorporate the text into the image.

CAUTION: Some laminates such as Formica may cause the surface to behave like a permanent adhesive after time.

Not recommended for exterior vehicle use.

Customers should make their own assessment regarding suitability.

Recommended conditions for use: 10°C - 30°C, 30% - 70% RH

for storage: 10°C - 30°C, 20% - 50% RH

Material Handling, and Shelf Life: 9 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com