

Hydroprint Glass Clear Self-Adhesive Extra Perm S053HCXP



Product Data

Product type: Self Adhesive Toner optimised print receptive polyester film

Appearance: Clear

Surface finish: Gloss clear coating

Physical characteristics:

	Typical Value	Test method
Front Face Thickness μ	53	Electronic micrometer
Total Thickness μ	155	Electronic micrometer
Total Weight (gsm)	205	Internal method

Compatibility:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour, including, for example, HP Laserjet 4xxx and OKI 93xx.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material, which is beyond the rated capabilities of some devices.

Applications and characteristics

- Tear resistant, high stability, waterproof face film
- For glass clear 'no-label' effect
- High grab, high-tack permanent acrylic pressure sensitive adhesive for long duration or rough surface label applications
- Heavy duty paper release

Recommended conditions for use: 10°C - 30°C, 50% - 70% RH

for storage: 10°C - 30°C, 20% - 50% RH

Material Handling, and Shelf Life: 18 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.

Copyright Sensitisers Group 2005

Kernow Coatings Limited +44(0)1326 373147 e-mail: kc@sensitisers.com