

Solvent Light Canvas T180SLC



Product Data

Product type: Solvent printable light canvas

Appearance: Matt White

Surface finish: Ink receptive impregnation

Physical characteristics:

		Typical Value	Test method
Total Thickness μ		188	Electronic micrometer
Total Weight (gsm)		143	Internal method
CIE Coordinates	L*	96.0	DCI Spectraflash (D65 10 ⁰ UV incl.)
	a*	-0.3	
	b*	1.9	

Compatibility:

All UVC and silk screen Printers.

All Ecosol printers, Roland, Mimaki JV3, Seiko Colorpainter.

Hard Solvent printers require testing for specific inks.

For brilliant colours, ink settings must be optimised according to ink, printer and software instructions.

Applications and Characteristics:

- § 100% Woven polyester fabric
- § Low cost alternative to cotton canvas
- § Stay flats, resist creasing and cracking
- § Suitable for...
 - Light display banners
 - Textile wall hangings
 - Exhibition drapes and roll-ups
 - Curtains
 - Indoor & Outdoor use

Recommended conditions for use: 10°C - 30°C, 30% - 70% RH

for storage: 5°C - 30°C, 20% - 70% RH

Material Handling, and Shelf Life: 24 Months

NOTICE The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. You must satisfy yourself as to the suitability of this product for your application. No responsibility for any loss as a result of any person placing reliance on any material contained herein can be accepted.